

1500 series

General Handheld Scanner



		Linear Imager	Laser	2D Imager	
Category		1500, 1500WA	1502	1504	
RF Communication of Bluetooth® scanner	Corded	1560	1562	1564	
	Bluetooth® cordless	1560	1562	1564	
	Module	Bluetooth® Class 2 (2.4 GHz) Version 2.0+EDR			
	Coverage	90 m ² / 295 ft. line of sight			
	Standard profile	SPP, HID			
Performance	Optical sensor	2500 pixels	Laser	752 x 480 pixels	
	Light source	Red LED 625 nm (1560: Red LED 618-626 nm)	Visible laser diode at 650 ± 15 nm	625 ± 5 nm LEDs (2x)	
	Resolution	3 mil	4 mil	3 mil - 1D barcode / 5 mil - 2D barcode	
	Depth of field 13 mil barcode	0.5 to 35 cm / 0.2 to 13.8 in. (1500WA: long barcode 8.2 cm, 8 mil- 7.5 to 14.5cm / 3 to 5.7 in.)	2 to 57 cm / 0.8 to 22.4 in.	Code 39 3 mil: 6.9 to 10.7 cm / 2.7 to 4.2 in. Code 39 5 mil: 3.6 to 18.5 cm / 1.4 to 7.3 in. UPCA 13 mil: 4.0 to 30.5 cm / 1.6 to 12 in. PDF417 5 mil: 7.1 to 11.4 cm / 2.8 to 4.5 in. PDF417 6.67 mil: 4.8 to 17.5 cm / 1.9 to 6.9 in.	
	Scanning angle	Pitch ± 70° Skew ± 70°	Pitch ± 65° Skew ± 50°	Pitch ±60° Skew±60°	
	PCS	Minimum 30%	Minimum 45%	Minimum 30%	
	Scan rate	200 scans, decodes / second (1500WA: 100 scans / second)	100 scans / second	60 scans / second	
	Ambient illumination	100,000 lux			
	Hands-free scanning	Auto-sense and continuous modes	Continuous mode	Auto-sense mode, and presentation mode	
	Barcodes support	Codabar, Code 39, Code 93, Code 128, GS1 DataBar (RSS), Industrial 2 of 5, Interleave 2 of 5, ISBT-128, Italian and French Pharmacodes, Matrix 2 of 5, MSI, Plessey, Telepen, UPC-A, UPC-E, EAN-8, EAN-13, GS1-128 (EAN-128)		1D: All major codes ² 2D: PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal Dutch Postal (KIX)	
	Programmable features	Data editing, interface selection, symbology configuration			
	Language support	US and UK English, French, Italian, Belgian, Norwegian, Swedish, Spanish, Portuguese, German, Japanese and Turkish			
	Physical	Dimension L x W x H	15.3 x 6.1 x 9.3 cm / 6.0 x 2.4 x 3.7 in.		
Weight without cable / with battery		145 g / 5.1 oz. (1560: 173 g / 6.1 oz.)	1502: 149 g / 5.2 oz. 1562: 177 g / 6.2 oz.	1504: 154 g / 5.4 oz. 1564: 185 g / 6.5 oz.	
Color		Black			
Switch		Tactile Switch			
Electrical	Memory for Bluetooth® scanner reserver buffer / batch mode	4 K / 512 K		10 K / 4 MB	
	Working hours for Bluetooth® scanner	24 / 12 hours depending on the CCD Sensor mode setting (Always Active function disabled/ Always Active function enabled, default setting)	24 hours based on 1 scans / 5 seconds	16 hours based on 1 scans / 5 seconds	
	Voltage	+5 V ±10% / 3.7 V 800 mAh Li-ion battery			
	Power consumption ³ Standby / Operating	50 mA / 265 mA (1560: 45 mA / 270 mA)	1502: 35 mA / 210 mA 1562: 25 mA / 210 mA	1504: 30 mA / 280 mA 1564: 35 mA / 230 mA	
User Environment	Temperature	Operating: 0°C to 50°C / 32°F to 122°F Storage: -20°C to 60°C / -4°F to 140°F (w/o battery)			
	Humidity	Operating: 10% to 90% Storage: 5% to 95%			
	Impact resistance	1.5 m (4.9 ft) multiple drops onto concrete (1560: 1.2 m (3.9 ft) multiple drops onto concrete)	1.2 m (3.9 ft) multiple drops onto concrete		
	Ingress protection	IP30			
	Electrostatic discharge	±8 kV contact ±15 kV air			
	EMC regulation	1500: BSMI, CE, C-tick, FCC, IC, KC 1500WA: BSMI, CE, C-tick, FCC, IC 1560: BSMI, CE, C-tick, FCC, IC, KC, NCC, SRMC, TELECOM	1502: BSMI, CE, C-tick, FCC, IC, KC 1562: BSMI, CE, C-tick, FCC, IC, KC, NCC, SRMC, TELECOM	1504: BSMI, CE, C-tick, FCC, IC, KC 1564: BSMI, CE, C-tick, FCC, IC, NCC, KC, SRMC, TELECOM	
Configuration	Setup options include Windows-based ScanMaster software, by direct connection or printing out barcode settings				
Accessories	USB, RS232 and keyboard wedge cables, hands-free adjustable stand Three-way desk/wall/auto-sense stand with optional weighted base, communication stand for Bluetooth® scanner provides Bluetooth® communication for up to 7 scanners, single battery charger for Bluetooth® scanner				
Warranty	5 years (1560: 3 years)		3 years (engine 1 year)		

1.It is based on communication stand without weighted base. 2.All of the barcodes that 1500 series 2D scanners can read except French Pharmacode, Plessey, and Telepen. 3.The data is tested with USB interface.



HEADQUARTERS
CipherLab Co., Ltd.
12F, 333 Dunhua S. Rd., Sec.2
Taipei, Taiwan 10669
Tel +886 2 8647 1166
Fax +886 2 8732 3300
www.cipherlab.com

CipherLab Electronics Trading
(Shanghai) Co., Ltd.
J Room, 4F, No.728 West Yan'an Rd.
Changning District, Shanghai
China 200050
Tel +86 21 3368 0288
Fax +86 21 3368 0286

CipherLab USA Inc.
2552 Summit Ave.
Plano, Texas USA 75074
Tel +1 469 241 9779
Toll Free 888 300 9779
Fax +1 469 241 0697

CipherLab GmbH
Willicher Damm 145
41066 Mönchengladbach
Germany
Tel +49 2161 56230 0
Fax +49 2161 56230 22